

# Agri Pro Trailing Shoe



- The Agri Pro Trailing Shoe provides soil engagement with an enhanced contour following
- Includes a 30-hole distributor, stone trap system and 40mm hose.
- The Agri Pro provides precise application and flotation system on hilly or uneven ground keeping downward force on the shoes and includes a self-levelling boom that adjust to the ground.

The Agri Pro gives the operator the option of filling from directly behind the applicator into the tank and is complete with mounting brackets between the tank and applicator sufficiently mounting onto the tank via a linkage system.

- The use of slurry applicators is one of the biggest opportunities to capitalize on precision nutrient application to further increase the value of the nutrient dense slurry
- Low emission slurry spreading offers up to 60% reduction in nitrogen loss on farm.

Size	HP Required	Gross Weight	Maximum Transport Width	Maximum Transport Height	Central Distributor
7.7m	75Hp	900kg	2.6m	3.3m	Standard

# Agri Pro Trailing Shoe LESS Applicator

A

Splash plate  
assembly

B

40mm unrestricted  
hosing

D

C

Steel tip boots for  
precise application  
below the canopy  
of the grass.

D

Central Distributor  
effortlessly chops  
and distributes  
evenly through 30  
pipes

E

B

E

Self-levelling boom  
and flotation system  
keeps downward  
force on the shoes

C

